



# POWER REVERSIBLE SNOW PLOW BH MODEL



N15921 SCHUBERT ROAD | GALESVILLE, WI 54630  
608-539-4600 | [www.universaltruckequipment.com](http://www.universaltruckequipment.com)

**SPECIALIZING IN THE MANUFACTURING OF PREMIUM SNOW PLOWS**

The BH model plow is the most common plow setup. This model is most commonly used by counties & cities who need a more aggressive attack angle which is good for asphalt applications. The BHW model is best for towns & villages that require a less aggressive attack angle due to gravel or seal coated roads. Going to a BHW still has the benefits of a BH model, just modified to fit your application.



# ADVANTAGES

- Single Cylinder with the Pivot Point Behind It, Allows the Plow to Swing Faster
- With the Pivot Point Located Behind the Cylinder. It Has As Much Or More Power Than Comparable Plow With Dual Cylinders
- 1 Piece Formed Construction of Semi-Circle Allows Plow to Be Mounted with Less Overhang on Front of Truck
- Plow Lifts Level and Reverses Level
- Power Reverse Cylinder is Designed to Permit Overhaul Using Standard Tools
- Moldboard Extension Springs are Tension Adjustable
- Single Cylinder Keeps Plow Closer to Truck

# STANDARD FEATURES

- Full Moldboard Trip with 4 Extension Springs
- 10'/11'/12' Standard Plow Lengths
- 40"/43"/46"/48" Plow Heights
- 10 GA. Moldboard with 6 Ribs
- Push Frame is 66" Wide and Constructed with 1/2"x4"x8" Angle Iron with 4 Hinge Points (Option for Heavy Duty Push Frame)
- One Heavy Duty 4" x 13" Cylinder with 2" Nitrided Rod
- Cylinder is Mounted Above the Push Frame
- Replaceable Brass Bushing & Grease Zerk at Live End of Cylinder for Extended Wear
- Heavy Duty Moldboard Hinges
- Lower Angle is Drilled for Standard & Carbide Blades (A.A.S.H.O. Punching)
- Power Reversible
- Attack Angle is Set at 20 Degrees (Non-Adjustable)

# POPULAR OPTIONS

- Trip Cutting Edge or Combination Moldboard Trip/Trip Edge
- Heavy Duty Push Frame is 112" Wide with 8 Ribs and 6 Hinge Points
- Various Hitches Available (Truck and Plow Portions)
- Rubber Snow Deflector
- Plow Markers
- Parking Stand
- Snow Wheels
- Carbide Blades
- Adjustable Shoes  
Standard or Ni-Hard in Mushroom Style or Flat
- DXV Custion Valve to Protect Reversing Sylinders
- Available in BHW Model (Warped Board) Height is 46".  
Moldboard has larger curl/belly and a more relaxed cutting edge angle (approximately 26 degrees). This Design will throw snow better and is more suitable for gravel and seal coated roads.

SPECIFICATIONS			
Moldboard Length	10'	11'	12'
Height	40" / 43"	40" / 43" / 46" / 48"	40" / 43" / 46" / 48"
Ribs	(6) 1/2" x 4"	(6) 1/2" x 4"	(6) 1/2" x 4"
Width of Cut in Degrees	35 Degrees = 8' 2"	35 Degrees = 9'	35 Degrees = 9' 10"
Moldboard Gauge	10 GA.	10 GA.	10 GA.
Trip Springs	4 Extension Type	4 Extension Type	4 Extension Type
Weight	EST. 1665# (43")	EST. 1865# (43")	EST. 1935# (43")
Bottom Angle (Frog)	3/4" x 4" x 4"	3/4" x 4" x 4"	3/4" x 4" x 4"