

# UNIVERSAL

## ALL HYDRAULIC JR. WING

P.D.F. / POWER DOWN FRONT



UNIVERSAL MODEL AHW/PDJM  
7' JR. WING (MID-MOUNT)

### STANDARD FEATURES:

- MID-MOUNTED OR REAR MOUNTED BEHIND SCRAPER
- ALL HYDRAULIC
- 6'7'/8' STANDARD LENGTHS
- 27" MOLDBOARD HEIGHT
- 3/16" THICK MOLDBOARD WITH 5 RIBS FULLY WELDED
- 3" X 6" TOE CYLINDER WITH 2" NITRIDED ROD - 6" STROKE
- 3" X 10" DECEL HEEL CYLINDER WITH 1-1/4" NITRIDED ROD WITH HYDRAULIC RESTRICTOR VALVES TO ADJUST THE SPEED OF THE WING UP AND DOWN
- 1-1/4" MAIN PIVOT BOLT
- 7-1/2" OF FLOAT AT THE TOE
- FLOATING LINK ARM AT THE HEEL
- 3/8" X 4" X 4" LOWER ANGLE WITH REINFORCING GUSSETS
- HEAVY DUTY ADJUSTABLE SPRING LOADED PUSH BEAM WITH SHEAR PIN
- SAFETY CHAIN AT THE TOE
- SAFETY CHAIN WITH REAR STOP
- A.A.S.H.O. STANDARD PUNCHING ON ALL BLADES

UNIVERSAL TRUCK EQUIPMENT  
N1592I SCHUBERT RD. GALESVILLE, WI 54630  
PHONE 608-539-4600 / FAX 608-539-4800  
[www.universaltruckequipment.com](http://www.universaltruckequipment.com)





**UNIVERSAL MODEL AHW/PDJS  
8' JR. WING (REAR MOUNTED)**

## **FEATURES/BENEFITS:**

- JR. WING IS COMPACT YET HEAVY DUTY, USING ALL HIGH STRENGTH STEEL AND THE LATEST HYDRAULIC TECHNOLOGIES
- FOLDS CLOSEST TO TRUCK OF ALL WINGS OF THIS TYPE AND SIZE
- NO WINDSHIELD "BLIND SPOT" - A SIGNIFICANT SAFETY FEATURE
- OPERATOR CAN SEE WING IN BOTH CARRY AND WORKING POSITIONS
- CAN BE INSTALLED ON ANY TRUCK WITH A C/A OF 84" OR GREATER
- WING CAN BE USED TO DO SOME BENCHING, SHOCK CUSHIONED REAR PUSH BEAM
- WING COMES STANDARD WITH DECEL HEEL LIFT CYLINDER
- CAN BE ORDERED WITH UNIVERSAL'S TRIP CUTTING EDGE
- DUMP BOX CAN BE RAISED WHEN WING IS IN THE CARRY POSITION



NI592I SCHUBERT RD. GALESVILLE, WI 54630  
PHONE 608-539-4600 / FAX 608-539-4800  
[www.universaltruckequipment.com](http://www.universaltruckequipment.com)