

Universal

TAILGATE SANDER

UTGS

STANDARD:

- FULL $\frac{3}{8}$ " THICK FLIGHTING
- FLIGHTING IS WELDED TO A 2 $\frac{1}{2}$ " I.D. AND 2 $\frac{7}{8}$ " O.D. SCHEDULE 40 PIPE, SUPPORTED BY 1 $\frac{1}{2}$ " SHAFTS
- BALL TYPE BEARINGS ARE 1 $\frac{1}{4}$ " DIAMETER & ARE GREASEABLE, MOUNTED WITH A 4 BOLT FLANGE
- END PLATES ARE $\frac{1}{4}$ " S/S - 14 $\frac{1}{4}$ " HIGH
- BOTTOM OPENS WITH 5 HINGE POINTS FOR EASY CLEAN OUT
- LEFT SELF LEVELING ADJUSTABLE SPINNER ASSEMBLIES WITH 18" POLY SPINNERS
- FULL 270-DEGREE OPENING COVER PLATE FOR EASY ACCESS – ONCE SAFETY INTERLOCK IS REMOVED
- SAFETY INTERLOCKS
- CLEAN-OUT DOOR OPENS TO THE TOP WITH LOCKS TO HOLD IN RAISED POSITION
- A STATIONARY SHIELD IN FRONT OF THE SPINNER PROTECTS THE UNDERCARRIAGE FROM THROWN MATERIAL
- DIRECT DRIVE
- SEAL SAVERS ON SPINNER AND AUGER
- STANDARD TAILGATE SPILL SHIELDS INSTALLED ON INSIDE OF TAILGATE: 31 $\frac{1}{2}$ " – 10 GA.
- ONE YEAR PARTS & LABOR WARRANTIES



OPTIONS:

- STAINLESS STEEL OR MILD STEEL
- 6" OR 9" AUGER
- STEEL SPINNER
- 4" AUGER FLIGHTING
- DUAL SPINNER ASSEMBLY
- BERM CHUTE
- WELD COUNTY NUMBERS

SPECS & CAPACITY CHART

	6" AUGER	9" AUGER
HEIGHT (W/SPINNER)	TBD	43"
HEIGHT (W/OUT SPINNER)	TBD	27.75"
WIDTH (W/SPINNER)	TBD	20"
WIDTH (W/OUT SPINNER)	TBD	20"
OVERALL LENGTH (APPROX.)	96.0"	96.0"
UNIT WEIGHT (APPROX.)	TBD	600 LBS.
SPINNER DIAMETER	18.0"	18.0"
SPINNER RPM	550 MAX.	550 MAX.
TROUGH MATERIAL	7-GA	7-GA
END PLATES	.25"	.25"