UNIVERSAL

CST MODEL

POWER REVERSIBLE SNOW PLOW



UNIVERSAL MODEL CST-II-43L

(SHOWN WITH SOME OPTIONS)

STANDARD FEATURES:

- FULL MOLDBOARD TRIP W/ 2 COMPRESSION SPRINGS
- ' IO'/II'/I2' STANDARD PLOW LENGTHS
- 40"/43"/48" PLOW HEIGHTS
- ' IO GA. MOLDBOARD WITH 8 RIBS
- PUSH FRAME IS 102" WIDE AND CONSTRUCTED WITH
 - 3/8" X 4" X 4" SQUARE TUBING W/ 6 HINGE POINTS
- PUSH FRAME SEMI CIRCLE IS 1/2" X 3-1/2" X 3-1/2" ANGLE
 TWO HEAVY DUTY 4" X 10" CYLINDERS W/ 2" NITRIDED RODS
- CYLINDERS ARE MOUNTED ABOVE THE PUSH FRAME
- DXV CUSHION VALVE TO PROTECT REVERSING CYLINDERS
- HEAVY DUTY MOLDBOARD HINGES
- A.A.S.H.O. PUNCHING ON STANDARD & CARBIDE BLADES
- POWER REVERSIBLE
- ADJUSTABLE ATTACK ANGLES 5 / 10 / 20 DEGREES (SET AT 20 DEGREES FROM FACTORY)

OPTIONS:

- TRIP CUTTING EDGE OR COMBO MOLDBOARD TRIP/TRIP EDGE
- VARIOUS HITCHES AVAILABLE (TRUCK AND PLOW PORTIONS)
- RUBBER SNOW DEFLECTOR
- PLOW MARKERS
- CARBIDE BLADES
- * ADJUSTABLE SHOES

STANDARD OR NI-HARD IN MUSHROOM STYLE OR FLAT

UNIVERSAL TRUCK EQUIPMENT NI592I SCHUBERT RD. GALESVILLE, WI 54630

PHONE 608-539-4600 / FAX 608-539-4800

www.universaltruckequipment.com





UNIVERSAL MODEL CST-I2-43L

UNIVERSAL MODEL CST-I2-435L

SPECIFICATIONS:		
MOLDBOARD LENGTH	11'	12'
HEIGHT	40" / 43" / 48"	40" / 43" / 48"
RIBS	(8) 1/2" x 4"	(8) 1/2" x 4"
WIDTH OF CUT IN DEGREES	35 DEGREES = 9' 8"	35 DEGREES = 10' 6"
MOLDBOARD GAUGE	10 GA.	10 GA.
TRIP SPRINGS	2 COMPRESSION TYPE	2 COMPRESSION TYPE
WEIGHT	EST. 2060# (43")	EST. 2125# (43")
BOTTOM ANGLE (FROG)	3/4" x 4" x 4"	3/4" x 4" x 4"

ADVANTAGES:

- PUSH FRAME WIDTH @ IO2" EXCEEDS ALL OTHER COMPARABLE PLOWS
- POWER REVERSE CYLINDERS ARE DESIGNED TO PERMIT OVERHAUL USING STANDARD TOOLS
- CYLINDERS MOUNTED ABOVE THE PUSH FRAME
 ALLOWS EASY ACCESS FOR MAINTENANCE AND ALSO
 REDUCES SAND-BLAST EFFECT OF ROAD MATERIAL



UNIVERSAL MODEL CST-I2-43L

(shown with mushroom style shoes)

