UNIVERSAL

OWUTA MODEL ONE WAY SNOW PLOWS



(BIG ONE WAY - POWER REVERSE - BREAK FORMED MOLDBOARD

STANDARD FEATURES:

2 MOLDBOARDS:

- * 3/I6" BREAK FORMED MOLDBOARD
- 'IO GA. SMOOTH ROLLED MOLDBOARD
- FULL MOLDBOARD TRIP WITH FOUR (4) EXTENSION TYPE SPRINGS W/ GREASABLE PIVOT POINTS
- II' PLOW/ 30"- 33" PLOW HEIGHT @ INLET END/ 50"-58" PLOW HEIGHT @ OUTLET END
- ' I2' PLOW/30"- 33" PLOW HEIGHT @ INLET END/ 54"-60" PLOW HEIGHT @ OUTLET END
- 12' PLOW HAS (8) 1/2" FLAME CUT RIBS INCLUDING ENDPLATE
- ' II' PLOW HAS (7) I/2' FLAME CUT RIBS INCLUDING ENDPLATE
- PUSH FRAME IS 117" WIDE AND CONSTRUCTED W/ 3/8" X 4" X 4" SQUARE TUBING W/ 6 HINGE POINTS
- FIXED ANGLE SET AT 35 DEGREES (SEE OPTIONS FOR POWER REVERSE CYLINDERS W/ A FRAME)
- ADJUSTABLE ATTACK ANGLE SET AT APPROX. 30 DEGREES FROM FACTORY
- 3/4" X 4" X 4" LOWER ANGLE W/ REINFORCING GUSSETS ON 12" CENTERS
- 5/8" X 8" CUTTING EDGE WITH STANDARD AASHO PUNCH
- VARIOUS HITCHES AVAILABLE



UNIVERSAL

OWUTA MODEL
ONE WAY SNOW PLOWS



UNIVERSAL MODEL OWUTA-I2-54L PR
(POWER REVERSE / IO GA. SMOOTH ROLLED MOLDBOARD)

OPTIONS:

- POWER REVERSE A-FRAME IN LIEU OF FIXED ANGLE
- TWO HEAVY DUTY 4" X 19" POWER REVERSING CYLINDERS WITH 2" NITRIDED RODS

 CYLINDERS ARE MOUNTED ABOVE THE PUSH FRAME, DEAD END OF CYLINDERS ARE EQUIPPED

 WITH BRASS BUSHINGS FOR EXTENDED WEAR
- RUBBER SNOW DEFLECTOR
- PLOW END MARKERS
- CARBIDE CUTTING EDGE
- DXV CUSHION VALVE TO PROTECT THE CYLINDERS
- PIN TYPE ADJUSTABLE PARKING STAND
- ADJUSTABLE SHOES

STANDARD OR NI-HARD MUSHROOM OR FLAT STYLE

- LONGER PLOW LENGTHS AVAILABLE UPON REQUEST
- CURB SHOE / CUTTING EDGE SHOE
- GUARDRAIL CUT ON OUTLET END

